

## **TUUBI**



Oil Pattern Distance Forward Oil Total Tank Configuration 40 11.24 mL N/A Reverse Brush Drop Reverse Oil Total Tank A Conditioner 30 10.28 mL Fire Oil Per Board Volume Oil Total Tank B Conditioner 40 ul 21.52 mL Curve

	START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL	
1	3L	3R	1	10	3	Α	35	0.0	0.0	0.0	1400	
2	4L	5R	2	14	3	Α	64	0.0	3.9	3.9	2560	
3	7L	7R	3	14	3	Α	81	3.9	9.8	5.9	3240	
4	8L	8R	2	14	3	Α	50	9.8	13.7	3.9	2000	
5	11L	11R	2	18	3	Α	38	13.7	18.8	5.1	1520	
6	14L	14R	1	18	3	Α	13	18.8	21.3	2.5	520	
7	3L	3R	0	18	3	Α	0	21.3	40.0	18.7	0	

3 11L 11R 1 18 3 B 19 27.5 25.0 -2.5 76 4 10L 10R 2 18 3 B 42 25.0 19.9 -5.1 168 5 9L 9R 2 18 3 B 46 19.9 14.8 -5.1 184 6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 206 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 216 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 132	2 14L 14R 1 18 3 B 13 30.0 27.5 -2.5 520 3 11L 11R 1 18 3 B 19 27.5 25.0 -2.5 760 4 10L 10R 2 18 3 B 42 25.0 19.9 -5.1 1680 5 9L 9R 2 18 3 B 46 19.9 14.8 -5.1 1840 6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 2000 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 2160 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 1320		START	STOP	LOADS	SPEED	BUFFER	TANK	CROSSED	START	END	FEET	T.OIL
3 11L 11R 1 18 3 B 19 27.5 25.0 -2.5 76 4 10L 10R 2 18 3 B 42 25.0 19.9 -5.1 168 5 9L 9R 2 18 3 B 46 19.9 14.8 -5.1 184 6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 206 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 216 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 132	3 11L 11R 1 18 3 B 19 27.5 25.0 -2.5 760 4 10L 10R 2 18 3 B 42 25.0 19.9 -5.1 1680 5 9L 9R 2 18 3 B 46 19.9 14.8 -5.1 1840 6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 2000 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 2160 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 1320	1	2L	2R	0	30	3	В	0	40.0	30.0	-10.0	0
4 10L       10R       2       18       3       B       42       25.0       19.9       -5.1       168         5 9L       9R       2       18       3       B       46       19.9       14.8       -5.1       184         6 8L       8R       2       14       3       B       50       14.8       10.9       -3.9       200         7 7L       7R       2       14       3       B       54       10.9       7.0       -3.9       210         8 4L       4R       1       10       3       B       33       7.0       5.6       -1.4       132	4       10L       10R       2       18       3       B       42       25.0       19.9       -5.1       1680         5       9L       9R       2       18       3       B       46       19.9       14.8       -5.1       1840         6       8L       8R       2       14       3       B       50       14.8       10.9       -3.9       2000         7       7L       7R       2       14       3       B       54       10.9       7.0       -3.9       2160         8       4L       4R       1       10       3       B       33       7.0       5.6       -1.4       1320	2	14L	14R	1	18	3	В	13	30.0	27.5	-2.5	520
5     9L     9R     2     18     3     B     46     19.9     14.8     -5.1     184       6     8L     8R     2     14     3     B     50     14.8     10.9     -3.9     200       7     7L     7R     2     14     3     B     54     10.9     7.0     -3.9     210       8     4L     4R     1     10     3     B     33     7.0     5.6     -1.4     132	5     9L     9R     2     18     3     B     46     19.9     14.8     -5.1     1840       6     8L     8R     2     14     3     B     50     14.8     10.9     -3.9     2000       7     7L     7R     2     14     3     B     54     10.9     7.0     -3.9     2160       8     4L     4R     1     10     3     B     33     7.0     5.6     -1.4     1320	3	11L	11R	1	18	3	В	19	27.5	25.0	-2.5	760
6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 200 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 210 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 132	6 8L 8R 2 14 3 B 50 14.8 10.9 -3.9 2000 7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 2160 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 1320	4	10L	10R	2	18	3	В	42	25.0	19.9	-5.1	1680
7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 210 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 132	7 7L 7R 2 14 3 B 54 10.9 7.0 -3.9 2160 8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 1320	5	9L	9R	2	18	3	В	46	19.9	14.8	-5.1	1840
8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 132	8 4L 4R 1 10 3 B 33 7.0 5.6 -1.4 1320	6	8L	8R	2	14	3	В	50	14.8	10.9	-3.9	2000
		7	7L	7R	2	14	3	В	54	10.9	7.0	-3.9	2160
	9 3L 3R 0 10 3 B 0 5.6 0.0 -5.6 0	8	4L	4R	1	10	3	В	33	7.0	5.6	-1.4	1320
9 3L 3R 0 10 3 B 0 5.6 0.0 -5.6		9	3L	3R	0	10	3	В	0	5.6	0.0	-5.6	0

Cleaner Ratio Main Mix 24:1 Forward
Cleaner Ratio Back End Mix 24:1 Reverse
Cleaner Ratio Back End Distance 59 Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Mlddle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	5	1.29	1.02	1.02	1.29	5.5



